



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Crown-Lok Part B

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Use of the substance/mixture : For RX only

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer:

Reliance Orthodontic Products, Inc. 1540 West Thorndale Ave.
Itasca, IL 60143 USA
630-773-4009, during normal business hours
www.RelianceOrthodontics.com

EC Representative:

Emergo Europe, Prinsessgracht 20
2514 AP The Hague, The Netherlands

Australian Sponsor: Emergo Australia, 201 Sussex St.

Darling Park, Tower II, Level 20
Sydney, NSW 2000 Australia

1.4. Emergency telephone number

Emergency number : CHEMTREC - 24-Hour Hazmat Emergency Communications Center
Domestic: 1-800-424-9300 Outside the U.S.: 1-703-527-3887, collect calls accepted

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317

Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) : 

GHS07

Signal word (CLP) : Warning
Hazardous ingredients : Proprietary; 2-Hydroxyethyl Methacrylate; BisGMA; Dibenzoyl Peroxide
Hazard statements (CLP) : H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
Precautionary statements (CLP) : P261 - Avoid breathing vapours
P264 - Wash hands thoroughly after handling
P272 - Contaminated work clothing should not be allowed out of the workplace
P280 - Wear protective gloves, eye protection, face protection
P302+P352 - IF ON SKIN: Wash with plenty of soap and water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

P321 - Specific treatment (see First aid measures on this label)
 P332+P313 - If skin irritation occurs: Get medical advice/attention
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
 P337+P313 - If eye irritation persists: Get medical advice/attention
 P362+P364 - Take off contaminated clothing and wash it before reuse
 P501 - Dispose of contents and container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation, a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste, a hazardous or special waste collection point.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Fused Silica	(CAS-No.) 60675-86-0	10 - 30	Skin Irrit. 2, H315
BisGMA	(CAS-No.) 1565-94-2	5 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
2-Hydroxyethyl Methacrylate	(CAS-No.) 868-77-9 (EC-No.) 212-782-2 (EC Index-No.) 607-124-00-X	5 - 10	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317
Proprietary	(CAS-No.) Proprietary (EC-No.) Proprietary	1 - 5	Skin Sens. 1B, H317
Dibenzoyl Peroxide	(CAS-No.) 94-36-0 (EC-No.) 202-327-6 (EC Index-No.) 617-008-00-0	< 1	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317
Proprietary	(CAS-No.) Proprietary (EC-No.) Proprietary (EC Index-No.) Proprietary	< 1	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Skin Corr. 1A, H314 Eye Dam. 1, H318 STOT SE 3, H335
Acetic Acid substance with a Community workplace exposure limit	(CAS-No.) 64-19-7 (EC-No.) 200-580-7 (EC Index-No.) 607-002-00-6	< 1	Flam. Liq. 3, H226 Skin Corr. 1A, H314

Specific concentration limits:

Name	Product identifier	Specific concentration limits
Proprietary	(CAS-No.) Proprietary (EC-No.) Proprietary (EC Index-No.) Proprietary	(C >= 1) STOT SE 3, H335
Acetic Acid	(CAS-No.) 64-19-7 (EC-No.) 200-580-7 (EC Index-No.) 607-002-00-6	(10 =<C < 25) Eye Irrit. 2, H319 (10 =<C < 25) Skin Irrit. 2, H315 (25 =<C < 90) Skin Corr. 1B, H314 (C >= 90) Skin Corr. 1A, H314

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
 First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
 First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
 First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.
 Symptoms/effects after eye contact : Eye irritation.

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing mist, vapours.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing mist, vapours.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Acetic Acid (64-19-7)		
EU	IOELV TWA (mg/m ³)	25 mg/m ³ (Acetic acid; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	10 ppm (Acetic acid; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m ³)	25 mg/m ³ (Acetic Acid; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	10 ppm (Acetic Acid; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	38 mg/m ³ (Acetic Acid; Belgium; Short time value)
Belgium	Short time value (ppm)	15 ppm (Acetic Acid; Belgium; Short time value)
France	VLE (mg/m ³)	25 mg/m ³ (Acetic Acid; France; Short time value;)
France	VLE (ppm)	10 ppm (Acetic Acid; France; Short time value;)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	25 mg/m ³ (Acetic Acid; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Acetic Acid (64-19-7)		
USA - ACGIH	ACGIH TWA (ppm)	10 ppm (Acetic acid; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
USA - ACGIH	ACGIH STEL (ppm)	15 ppm (Acetic acid; USA; Short time value; TLV - Adopted Value)
Proprietary (Proprietary)		
EU	IOELV TWA (mg/m ³)	8.4 mg/m ³ (Proprietary; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV TWA (ppm)	2 ppm (Proprietary; EU; Time-weighted average exposure limit 8 h; Indicative occupational exposure limit value)
EU	IOELV STEL (mg/m ³)	12.6 mg/m ³ (Proprietary; EU; Short time value; Indicative occupational exposure limit value)
EU	IOELV STEL (ppm)	3 ppm (Proprietary; EU; Short time value; Indicative occupational exposure limit value)
Belgium	Limit value (mg/m ³)	4.2 mg/m ³ (Proprietary; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Limit value (ppm)	1 ppm (Proprietary; Belgium; Time-weighted average exposure limit 8 h)
Belgium	Short time value (mg/m ³)	12.6 mg/m ³ (Proprietary; Belgium; Short time value)
Belgium	Short time value (ppm)	3 ppm (Proprietary; Belgium; Short time value)
France	VME (mg/m ³)	4.2 mg/m ³ (Proprietary; France; Time-weighted average exposure limit 8 h)
France	VME (ppm)	1 ppm (Proprietary; France; Time-weighted average exposure limit 8 h;)
France	VLE (mg/m ³)	12.6 mg/m ³ (Proprietary; France; Short time value;)
France	VLE (ppm)	3 ppm (Proprietary; France; Short time value;)
Netherlands	Grenswaarde TGG 8H (mg/m ³)	4.2 mg/m ³ (Proprietary; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 8H (ppm)	1 ppm (Proprietary; Netherlands; Time-weighted average exposure limit 8 h; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	12.6 mg/m ³ (Proprietary; Netherlands; Short time value; Public occupational exposure limit value)
Netherlands	Grenswaarde TGG 15MIN (ppm)	3 ppm (Proprietary; Netherlands; Short time value; Public occupational exposure limit value)
United Kingdom	WEL TWA (mg/m ³)	8 mg/m ³ Proprietary; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL TWA (ppm)	2 ppm Proprietary; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (mg/m ³)	17 mg/m ³ Proprietary; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
United Kingdom	WEL STEL (ppm)	4 ppm Proprietary; United Kingdom; Short time value; Workplace exposure limit (EH40/2005)
USA - ACGIH	Local name	Proprietary
USA - ACGIH	ACGIH TWA (ppm)	0.5 ppm
USA - ACGIH	ACGIH STEL (ppm)	1 ppm
USA - ACGIH	Remark (ACGIH)	URT irr; visual impair; Skin; A4
USA - OSHA	Local name	Proprietary
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	100 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	25 ppm
Dibenzoyl Peroxide (94-36-0)		
Belgium	Limit value (mg/m ³)	5 mg/m ³ (Dibenzoyl Peroxide; Belgium; Time-weighted average exposure limit 8 h)
France	VME (mg/m ³)	5 mg/m ³ (Dibenzoyl Peroxide; France; Time-weighted average exposure limit 8 h)
United Kingdom	WEL TWA (mg/m ³)	5 mg/m ³ Dibenzoyl peroxide; United Kingdom; Time-weighted average exposure limit 8 h; Workplace exposure limit (EH40/2005)

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Dibenzoyl Peroxide (94-36-0)		
USA - ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³ (Dibenzoyl Peroxide; France; Time-weighted average exposure limit 8 h); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Hand protection:

Protective gloves

Eye protection:

Protective goggles

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Environmental exposure controls:

Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Paste.
Colour	: White.
Odour	: Acrylic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: Not applicable
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable.
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: Not applicable
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: Not applicable

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

Proprietary (Proprietary)	
LD50 oral rat	> 2000 mg/kg bodyweight (Rat; Literature study)
LD50 dermal rat	> 2000 mg/kg bodyweight (Rat; Literature study)

Acetic Acid (64-19-7)	
LD50 oral rat	3310 mg/kg bodyweight (Rat; Other; Read-across)

Fused Silica (60675-86-0)	
LD50 oral rat	N/A
LD50 dermal rat	N/A
LD50 dermal rabbit	N/A
LC50 inhalation rat (ppm)	N/A
LC50 inhalation rat (Dust/Mist - mg/l/4h)	N/A mg/l/4h
LC50 inhalation rat (Vapours - mg/l/4h)	N/A mg/l/4h

2-Hydroxyethyl Methacrylate (868-77-9)	
LD50 oral rat	5564 mg/kg bodyweight (Rat; Experimental value)
LD50 dermal rabbit	> 5000 mg/kg bodyweight (Rabbit; Experimental value)

Proprietary (Proprietary)	
LD50 oral rat	> 460 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value; 730 mg/kg bodyweight; Rat)
LD50 dermal rabbit	416 mg/kg (Rabbit; Experimental value; Equivalent or similar to OECD 402; 580 mg/kg bodyweight; Rabbit)
LC50 inhalation rat (mg/l)	> 4.2 mg/l/4h (Rat)

Dibenzoyl Peroxide (94-36-0)	
LD50 oral rat	> 5000 mg/kg (Rat)

Skin corrosion/irritation : Causes skin irritation.

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

Fused Silica (60675-86-0)	
LOAEL (oral, rat)	N/A mg/kg bodyweight
LOAEL (dermal, rat/rabbit)	N/A mg/kg bodyweight
LOAEC (inhalation, rat, gas)	N/A ppmv/4h
LOAEC (inhalation, rat, vapour)	N/A mg/l/4h
LOAEC (inhalation, rat, dust/mist/fume)	N/A mg/l/4h

STOT-repeated exposure : Not classified

Fused Silica (60675-86-0)	
LOAEL (oral, rat, 90 days)	N/A mg/kg bodyweight/day

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Fused Silica (60675-86-0)	
LOAEL (dermal, rat/rabbit, 90 days)	N/A mg/kg bodyweight/day
LOAEC (inhalation, rat, gas, 90 days)	N/A ppmv/6h/day
LOAEC (inhalation, rat, vapour, 90 days)	N/A mg/l/6h/day
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	N/A mg/l/6h/day

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Not classified

Proprietary (Proprietary)	
LC50 fish 1	175 mg/l (LC50; 96 h)
LC50 fish 2	> 100 mg/l (LC50; EU Method C.1; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
EC50 Daphnia 1	> 100 mg/l (EC50; EU Method C.2; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	>= 100 mg/l (NOEC; EU Method C.2; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	> 100 mg/l (EC50; EU Method C.3; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)
Threshold limit algae 2	> 100 mg/l (EC50; EU Method C.3; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)

2-Hydroxyethyl Methacrylate (868-77-9)	
LC50 fish 1	227 mg/l (LC50; 96 h)
EC50 Daphnia 1	171 mg/l (NOEC; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
EC50 Daphnia 2	380 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	836 mg/l (ErC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)
Threshold limit algae 2	345 mg/l (EbC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Experimental value)

Proprietary (Proprietary)	
EC50 Daphnia 2	17 mg/l (LC50; ASTM; 48 h; Ceriodaphnia dubia; Semi-static system; Fresh water; Experimental value)

Dibenzoyl Peroxide (94-36-0)	
LC50 fish 1	2 mg/l (LC50; 96 h; Poecilia reticulata)

12.2. Persistence and degradability

Proprietary (Proprietary)	
Persistence and degradability	Readily biodegradable in water.

Acetic Acid (64-19-7)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 0.74 g O ₂ /g substance
Chemical oxygen demand (COD)	1.03 g O ₂ /g substance
ThOD	1.07 g O ₂ /g substance

2-Hydroxyethyl Methacrylate (868-77-9)	
Persistence and degradability	Readily biodegradable in water. Biodegradability in soil: no data available. Adsorbs into the soil.

Proprietary (Proprietary)	
Persistence and degradability	Readily biodegradable in water. Low potential for adsorption in soil. Photodegradation in the air.
Biochemical oxygen demand (BOD)	< 0.001 g O ₂ /g substance
Chemical oxygen demand (COD)	1.02 g O ₂ /g substance

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Dibenzoyl Peroxide (94-36-0)	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the substance available.

12.3. Bioaccumulative potential

Proprietary (Proprietary)	
Log Pow	0.75 (Calculated)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Acetic Acid (64-19-7)	
BCF fish 1	3.16 (BCF; Pisces)
Log Pow	-0.17 (Experimental value; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

2-Hydroxyethyl Methacrylate (868-77-9)	
BCF fish 1	1.3 - 1.5 (BCF)
Log Pow	-0.55 - 0.49 (0.42; Experimental value; OECD 107: Partition Coefficient (n-octanol/water); Shake Flask Method; 25 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Proprietary (Proprietary)	
BCF fish 1	< 0.5 (BCF; OECD 305: Bioconcentration: Flow-Through Fish Test; 42 days; Cyprinus carpio; Fresh water)
Log Pow	1.45 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

Dibenzoyl Peroxide (94-36-0)	
Log Pow	3.71 (QSAR; 3.2; Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 22 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

Acetic Acid (64-19-7)	
Surface tension	0.028 N/m (20 °C)
Log Koc	log Koc,0.06; QSAR
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.

Proprietary (Proprietary)	
Surface tension	0.021 N/m (20 °C)
Log Koc	log Koc,Other; 2.56; Calculated value

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : Not applicable
 UN-No. (IMDG) : Not applicable
 UN-No. (IATA) : Not applicable
 UN-No. (ADN) : Not applicable
 UN-No. (RID) : Not applicable

14.2. UN proper shipping name

Proper Shipping Name (ADR) : Not applicable
 Proper Shipping Name (IMDG) : Not applicable
 Proper Shipping Name (IATA) : Not applicable
 Proper Shipping Name (ADN) : Not applicable
 Proper Shipping Name (RID) : Not applicable

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : Not applicable

IMDG

Transport hazard class(es) (IMDG) : Not applicable

IATA

Transport hazard class(es) (IATA) : Not applicable

ADN

Transport hazard class(es) (ADN) : Not applicable

RID

Transport hazard class(es) (RID) : Not applicable

14.4. Packing group

Packing group (ADR) : Not applicable

Packing group (IMDG) : Not applicable

Packing group (IATA) : Not applicable

Packing group (ADN) : Not applicable

Packing group (RID) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

- Overland transport

No data available

- Transport by sea

No data available

- Air transport

No data available

- Inland waterway transport

No data available

- Rail transport

No data available

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

15.1.2. National regulations

Germany

VwVwS Annex reference : Water hazard class (WGK) 3, severe hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Crown-Lok Part B

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Netherlands

SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid	: None of the components are listed
NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling	: None of the components are listed

Denmark

Recommendations Danish Regulation	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product
-----------------------------------	---

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Org. Perox. B	Organic Peroxides, Type B
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1B	Skin sensitisation, category 1B
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H241	Heating may cause a fire or explosion
H302	Harmful if swallowed
H311	Toxic in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product